

## **Delta D333 Pipe Sealant**

Product code: D333 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

D333 Pipe Sealant

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Adhesives, sealants

### Uses advised against

Any non-intended use.

### 1.3. Details of the supplier of the safety data sheet

Company name: Delta Adhesives Limited

Place: Units 39-40 Claycliffe Business Park, Barnsley, S75 1JU, United Kingdom

Telephone: +44 (0)1226 381571

Internet: <a href="www.delta-adhesives.co.uk">www.delta-adhesives.co.uk</a>
Responsible Department: sales@delta-adhesives.co.uk

**1.4. Emergency telephone** +44 (0)1226 381571 (Mo-Fr, 08:00-16:00)

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant, N - Dangerous for the environment

R phrases:

Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## **GHS** classification

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory/skin sensitization: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

## Hazardous components which must be listed on the label

Polyglycol dimethacrylate dodecyl methacrylate tetradecyl methacrylate

Signal word: Warning

Pictograms: GHS07-GHS09



## **Delta D333 Pipe Sealant**

Product code: D333 Page 2 of 10





#### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container to in accordance with official regulations.

## 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## **Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Polyglycol dimethacrylate	40 - < 45 %
25852-47-5	R43-52-53	
	Skin Sens. 1, Aquatic Chronic 3; H317 H412	
205-570-6	dodecyl methacrylate	10 - < 15 %
142-90-5	Xi - Irritant, N - Dangerous for the environment R36/37/38-50-53	
607-247-00-9	Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H319 H335 H315 H400 H410	
219-835-9	tetradecyl methacrylate	5 - < 10 %
2549-53-3	Xi - Irritant R36/38-43	
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1; H319 H315 H317	
204-055-3	2'-Phenylacetohydrazide	< 1 %
114-83-0	T - Toxic, Xi - Irritant R25-36/37/38-43	
	Acute Tox. 3, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H301 H319 H335 H315 H317	

Full text of R and H phrases: see Section 16.

#### **Further Information**

Product does not contain listed SVHC substances.

# **SECTION 4: First aid measures**



## **Delta D333 Pipe Sealant**

Product code: D333 Page 3 of 10

## 4.1. Description of first aid measures

### **General information**

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).

#### After inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. Call a POISON CENTER or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Dry extinguishing powder. Foam. Water spray. Carbon dioxide (CO2).

# Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

## 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical resistant suit. In case of fire and/or explosion do not breathe fumes.

## **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray/stream to protect personnel and to cool endangered containers.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

Wear personal protection equipment. (refer to chapter 8)

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). In case of leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

## 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.



## **Delta D333 Pipe Sealant**

Product code: D333

Page 4 of 10

Treat the assimilated material according to the section on waste disposal. Clear contaminated area thoroughly.

### 6.4. Reference to other sections

See protective measures under point 7 and 8.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

Provide adequate ventilation.

Wear suitable protective clothing. ( Refer to chapter 8. )

## Advice on protection against fire and explosion

Usual measures for fire prevention.

## Further information on handling

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

General protection and hygiene measures: refer to chapter 8

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

### Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances.

#### Further information on storage conditions

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

## 7.3. Specific end use(s)

No information available.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## Additional advice on limit values

To date, no national limit values exist.

### 8.2. Exposure controls





#### Appropriate engineering controls

In case of open handling, use devices with built-in suction where possible. If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

## Protective and hygiene measures

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work. Remove contaminated clothing immediatley and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be used outside the work area. Street clothing should be stored seperately from work clothing. Protect skin by using skin protective cream.

## Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

## **Hand protection**

Pull-over gloves of rubber. DIN EN 374



## **Delta D333 Pipe Sealant**

Product code: D333 Page 5 of 10

Suitable material:

(Breakthrough time >= 480 min, penetration time (maximum wearing period): 160 min)

CR (polychloroprenes, Chloroprene rubber). (0,5 mm)

FKM (fluororubber). (0,4 mm)

Butyl rubber. (0,5 mm)

Before using check leak tightness / impermeability. In case of reutilization, clean gloves before taking off

and store in well-aired place.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

## Skin protection

Suitable protection of the body: Lab apron.

#### Respiratory protection

Respiratory protection required in case of:

insufficient ventilation.

Generation/formation of aerosols

Generation/formation of mist

Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Type: A / P2/P3

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Do not empty into drains or the aquatic environment.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: White

Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range: not determined Flash point: not determined

**Explosive properties** 

none/none

Lower explosion limits: not determined Upper explosion limits: not determined

**Oxidizing properties** 

none/none

Vapour pressure: not determined

Density: not determined

Viscosity / dynamic: not determined

### 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**



## **Delta D333 Pipe Sealant**

Product code: D333 Page 6 of 10

#### 10.1. Reactivity

No information available.

## 10.2. Chemical stability

Stable under normal storage and handling conditions.

## 10.3. Possibility of hazardous reactions

No information available.

#### 10.4. Conditions to avoid

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

## 10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents, strong. Alkalis (alkalis), concentrated.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### Toxicocinetics, metabolism and distribution

No information available.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

### **Acute toxicity**

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
114-83-0	2'-Phenylacetohydrazide				
	oral	LD50	270 mg/kg	Mouse.	

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

## Sensitising effects

May cause an allergic skin reaction. (Polyglycol dimethacrylate), (tetradecyl methacrylate), (2'-

Phenylacetohydrazide)

Respiratory or skin sensitisation:

People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

### STOT-single exposure

May cause respiratory irritation. (dodecyl methacrylate), (2'-Phenylacetohydrazide)

#### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Specific effects in experiment on an animal

No information available.

## **SECTION 12: Ecological information**

## 12.1. Toxicity



## **Delta D333 Pipe Sealant**

Product code: D333 Page 7 of 10

No data available

No data available

#### 12.3. Bioaccumulative potential

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
142-90-5	dodecyl methacrylate	6,68
2549-53-3	tetradecyl methacrylate	7,66

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects

No data available

#### **Further information**

Do not empty into drains or the aquatic environment.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### Advice on disposal

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal. Cleaned containers may be recycled.

## Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

## Waste disposal number of used product

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances Classified as hazardous waste.

### Waste disposal number of contaminated packaging

150110

WASTE PACKAGING: ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances Classified as hazardous waste.

# Contaminated packaging

Handle contaminated packaging in the same way as the substance itself.

9

### **SECTION 14: Transport information**

# Land transport (ADR/RID)

UN 3082 14.1. **UN** number:

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(dodecyl methacrylate)

14.3. Transport hazard class(es):



## **Delta D333 Pipe Sealant**

Product code: D333 Page 8 of 10

Ш 14.4. Packing group:

9 Hazard label:

М6 Classification code:

274 335 601 Special Provisions:

Limited quantity: 5 L Transport category: 3 Hazard No: 90 Tunnel restriction code: Ε

Other applicable information (land transport)

Excepted quantity: E1

Inland waterways transport (ADN)

14.1. UN number: UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping name:

(dodecyl methacrylate)

14.3. Transport hazard class(es):

Ш 14.4. Packing group:

Hazard label: 9



Classification code: M6

**Special Provisions:** 274 335 601

Limited quantity: 5 L

Other applicable information (inland waterways transport)

Excepted quantity: E1

Marine transport (IMDG)

UN 3082 14.1. UN number:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping name:

(dodecyl methacrylate)

14.3. Transport hazard class(es): 9

14.4. Packing group: Ш

Hazard label: 9



Marine pollutant: YES Special Provisions: 274, 335 Limited quantity: 5 L F-A, S-F EmS:

Other applicable information (marine transport)

Excepted quantity: E1

Air transport (ICAO)

UN 3082 14.1. UN number:



## **Delta D333 Pipe Sealant**

Product code: D333 Page 9 of 10

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(dodecyl methacrylate)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9

Special Provisions: A97 Å158 Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

Passenger-LQ: Y964 Excepted quantity: E1

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: dodecyl methacrylate

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

irrelevant

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU regulatory information** 

1999/13/EC (VOC): No information available. VOC Directive 2004/42/EC: No information available.

Additional information

The preparation is dangerous in the sense of Directive 1999/45/EC.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

Regulation 96/82/EC for danger control following severe accidents with dangerous substances: Appendix I,

Part 2, No 9ii, siehe StörfallVO (Seveso II). REACH 1907/2006 Appendix XVII, No 3

**National regulatory information** 

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

Changes

Rev. 1,00, 16.12.2014, Initial release



## **Delta D333 Pipe Sealant**

Product code: D333 Page 10 of 10

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

## Full text of R phrases referred to under Sections 2 and 3

25	Toxic if swallowed.
36/37/38	Irritating to eyes, respiratory system and skin.
36/38	Irritating to eyes and skin.
43	May cause sensitisation by skin contact.
50	Very toxic to aquatic organisms.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
52	Harmful to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.

## Full text of H statements referred to under Sections 2 and 3

H301	Toxic if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)