Regulation EC No 1907/2006 Art.31

Productname :	WHITE SPRAY GREASE				
Ref.Nr.:	UDS000421_3_20150923 (EN)				

Creationdate : Replaces: 23.09.15 Version : 1.0 UDS000421_20141222

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WHITE SPRAY GREASE Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Ambersil House - Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical:	Aerosols, category 1
	Extremely flammable aerosol.
	Pressurised container: May burst if heated.
Health:	Skin irritation, category 2
	Causes skin irritation.
	Specific target organ toxicity - single exposure, category 3
	May cause drowsiness or dizziness.
Environment:	Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

Classification according to 67/548/EEC or 1999/45/EC:

Health:

R38: Irritating to skin.



Safety Data Sheet		Regulation EC No 1907/2006 Art.31				
Productname :	WHITE SPRAY GREASE	Creationdate :	23.09.15 Version : 1.0			
Ref.Nr.:	UDS000421_3_20150923 (EN)	Replaces:	UDS000421_20141222			

	R67: Vapours may cause drowsiness and dizziness.
Physical:	R12: Extremely flammable.
-	EXTREMELY FLAMMABLE
Environment:	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier:	Contains: Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane
Hazard pictogram(s):	
Signal word:	Danger
Hazard statement(s):	H222 : Extremely flammable aerosol.
	H229 : Pressurised container: May burst if heated.
	H315 : Causes skin irritation.
	H336 : May cause drowsiness or dizziness.
	H412 : Harmful to aquatic life with long lasting effects.
Precautionary statement(s):	P102 : Keep out of reach of children.
	P210 : Keep away from heat, hot surfaces, sparks, open flames and other
	ignition sources. No smoking.
	P211 : Do not spray on an open flame or other ignition source.
	P251 : Do not pierce or burn, even after use.
	P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.
	P271 : Use only outdoors or in a well-ventilated area.
	P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
	P501-2 : Dispose of contents/container to an authorised waste collection point.

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	CAS-nr.	L0-111	%	-	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91- 4	270-990- 9			12	K,G
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	921-024- 6	<25	F,Xn,N	11-38-51/53-65- 67	В



2/9

Safety	Data	Sheet
--------	------	-------

Productname : Ref.Nr.:	WHITE SPRAY GREASE UDS000421_3_20150923 (EN)	Creationdate : Replaces:	23.09.15 Version : 1.0 UDS000421 20141222
		Replaceer	000000121_20111222

zinc oxide	1314-13-2	215-222- 5	<2	N	50/53	В
Explanation notes						
B : substance with national established workplace exposure limit						
G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						

Hazardous ingredient	Registration number	CAS- nr.	EC- nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	-	68512- 91-4	270- 990-9	30- 60	Press. Gas, Flam. Gas 1	H280,H220	K,G
Hydrocarbons, C6-C7, n- alkanes,isoalkanes,cyclics,< 5% n- hexane	01- 2119475514- 35	-	921- 024-6	<25	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	в
zinc oxide	01- 2119463881- 32	1314- 13-2	215- 222-5	<2	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	в
Explanation notes							
B : substance with national established w	orkplace exposi	ure limit					
G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006							

K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	If substance has got into eyes, immediately wash out with plenty of water If eye irritation persists: Get medical advice/attention.
Contact with skin :	Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Inhalation :	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion :	If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	Irritating to skin Symptoms : redness and pain
Eye contact :	May cause irritation. Symptoms : redness and pain



Safety Data Sheet		Regulation EC No 1907/2006 Art.31	
Productname :	WHITE SPRAY GREASE	Creationdate :	23.09.15 Version : 1.0
Ref.Nr.:	UDS000421_3_20150923 (EN)	Replaces:	UDS000421_20141222

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition Take precautionary measures against static discharges



4/9

Safety Data Sheet

Productname :	WHITE SPRAY GREASE	Creationdate :	23.09.15 Version : 1.0
Ref.Nr.:	UDS000421_3_20150923 (EN)	Replaces:	UDS000421_20141222

Equipment should be earthed Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Do not breathe aerosols or vapours. Ensure adequate ventilation Avoid contact with skin and eyes. Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Lubricants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

No information available

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. In all cases handle and use the product in accordance with good industrial hygiene practices. Ensure adequate ventilation
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
hands and skin :	When handling the product wear chemical-resistant gloves (standard EN 374). Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through.
Recommended gloves:	Nitrile
eyes :	Wear safety goggles.
Environmental protection:	Avoid release to the environment. Collect spillage.

SECTION 9: Physical and chemical properties



CRC Industries UK Limited Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

5/9

Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	WHITE SPRAY GREASE	Creationdate :	23.09.15 Version : 1.0	
Ref.Nr.:	UDS000421_3_20150923 (EN)	Replaces:	UDS000421_20141222	

9.1. Information on basic physical and chemical properties

(for aerosols data for the product	without propellant)
Apperance : physical state :	Propane/butane propelled liquid.
colour :	Off-white.
odour :	Characteristic odor.
рН :	Not applicable.
Boiling point/range :	63 °C
Flash point :	- 26 °C
Evaporation rate :	Not available.
Explosion limits : upper limit :	9.4 %
lower limit :	1.1 %
Vapour pressure :	Not available.
Relative density :	0.797 g/cm3 (@ 20°C).
Solubility in water :	Insoluble in water
Auto-ignition :	> 200 Not available.
Viscosity :	Not available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information



6/9

Safety Data Sheet	Regulation EC No 1907/2006 Art.31	

Productname :	WHITE SPRAY GREASE	Creationdate :	23.09.15 Version : 1.0
Ref.Nr.:	UDS000421_3_20150923 (EN)	Replaces:	UDS000421_20141222

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Irritating to skin
Eye contact :	May cause irritation.

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 25000 mg/m3
		LD50 derm.rat	> 2000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
zinc oxide	1314-13-2	LC50 fish	1.1 mg/l
		EC50 daphnia	0.098 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment



7/9

Safety Data Sheet		Regulation EC No 1	907/2006 Art.31
	ame : WHITE SPRAY GREASE UDS000421_3_20150923 (EN)		23.09.15 Version : 1.0 UDS000421_20141222
No information available			
2.6. Other adverse effects			
No information available			
SECTION 13: Disposal consid	derations		
13.1. Waste treatment methods			
Product :	Do not discha	arge into drains or the	t be disposed of in a safe way. environment, dispose to an authorised
Contaminated packaging :	waste collect Disposal sho	•	with local, state or national legislation
SECTION 14: Transport infor	mation		
14.1. UN number			
UN-number :	1950		
14.2. UN proper shipping name			
Proper shipping name:	AEROSOLS		
14.3. Transport hazard class(es)			
Class: ADR/RID - Classification code:	2.1 5F		
14.4. Packing group			
Packing group:	Not applicabl	le.	
14.5. Environmental hazards			
ADR/RID - Environmentally hazardous:	No		
IMDG - Marine pollutant: IATA/ICAO - Environmentally hazardous:	No		
14.6. Special precautions for user			
ADR/RID - Tunnelcode: IMDG - Ems: IATA/ICAO - PAX: IATA/ICAO - CAO	(D) F-D, S-U 203 203		
		8 / 9	

CRC Industries UK Limited Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

P

Regulation EC No 1907/2006 Art.31

Productname :	WHITE SPRAY GREASE
Ref.Nr.:	UDS000421_3_20150923 (EN)

Creationdate : Replaces: 23.09.15 Version : 1.0 UDS000421_20141222

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC. EU-directive 99/45/EC Regulation (EC) No 1272/2008 (CLP) Regulation (EC) No 1907/2006 (REACH)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases:	 R11: Highly flammable. R12: Extremely flammable. R38: Irritating to skin. R65: Harmful: may cause lung damage if swallowed. R67: Vapours may cause drowsiness and dizziness. R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
*Explanation hazard statements:	 H220 : Extremely flammable gas. H225 : Highly flammable liquid and vapour. H280 : Contains gas under pressure; may explode if heated. H304 : May be fatal if swallowed and enters airways. H315 : Causes skin irritation. H336 : May cause drowsiness or dizziness. H400 : Very toxic to aquatic life. H410 : Very toxic to aquatic life with long lasting effects. H411 : Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.



CRC Industries UK Limited Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6 4DD Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

9/9