Regulation EC No 1907/2006 Art.31

Productname:

Ref.Nr.:

Brake Cleaner

BDS000129 3 20141016 (EN)

Creationdate : Replaces: 16.10.14 Version : 2.0 BDS000129 20111223

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Brake Cleaner

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Health: Skin irritation, category 2

Causes skin irritation. Eye irritation, category 2 Causes serious eye irritation.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Environment: Hazardous to the aquatic environment, chronic category 2

Toxic to aquatic life with long lasting effects.

Other hazards: None



Regulation EC No 1907/2006 Art.31

Productname: **Brake Cleaner**

Ref.Nr.: BDS000129 3 20141016 (EN) Creationdate: 16.10.14 Version: 2.0 Replaces: BDS000129 20111223

Classification according to 67/548/EEC or 1999/45/EC:

EXTREMELY FLAMMABLE

Xi: IRRITANT

N: DANGEROUS FOR THE ENVIRONMENT

Health: R38: Irritating to skin.

R67: Vapours may cause drowsiness and dizziness.

Physical: **EXTREMELY FLAMMABLE**

Environment: R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:

hydrocarbons

Hazard pictogram(s):





Signal word: Danger

Hazard statement(s): H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statement(s): P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard

None information:

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.



Regulation EC No 1907/2006 Art.31

 Productname :
 Brake Cleaner
 Creationdate :
 16.10.14 Version : 2.0

 Ref.Nr.:
 BDS000129_3_20141016 (EN)
 Replaces:
 BDS000129_20111223

3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	921-024-6	30-60	F,Xn,N	11-38-51/53-65-67	В
Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0	10-30	F,Xn,N	11-51/53-65-66-67	В
Naphtha (petroleum), hydrodesulfurized light (benzene <0.1%)	92045-53-9	927-510-4	10-30	F,Xn,N	11-38-51/53-65-67	В
carbon dioxide	124-38-9	204-696-9	5-10	-	-	A,G
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	200-661-7	<10	F,Xi	11-36-67	В
acetone; propan-2-one; propanone	67-64-1	200-662-2	<10	F,Xi	11-36-66-67	Α
Explanation notes						
A : substance with Community workplace exposure limit						
B : substance with national established workplace exposure limit						
G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006						

Hazardous ingredient	Registration number	CAS- nr.	EC- nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	01- 2119475514- 35	-	921- 024-6		Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	В
Naphtha (petroleum), hydrotreated light	01- 2119473851- 33	64742- 49-0	920- 750-0	10- 30	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H336,H304,H411	В
Naphtha (petroleum), hydrodesulfurized light (benzene <0.1%)	01- 2119475515- 33	92045- 53-9	927- 510-4	10- 30	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	В
carbon dioxide		124-38- 9	204- 696-9	5-10	Press. Gas	H280	A,G
propan-2-ol; isopropyl alcohol ;isopropanol	01- 2119457558- 25	67-63-0	200- 661-7	<10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	В
acetone; propan-2-one; propanone	01- 2119471330- 49	67-64-1	200- 662-2	<10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	A

Explanation notes

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Contact with skin: Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.



Regulation EC No 1907/2006 Art.31

Productname :

Ref.Nr.:

Brake Cleaner

BDS000129_3_20141016 (EN)

Creationdate : Replaces:

16.10.14 Version : 2.0 BDS000129 20111223

Ingestion: If swallowed do not induce vomiting because of risk of aspiration into the lungs.

If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents may

induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: Irritating to skin

Symptoms: redness and pain

Eye contact: Irritating to eyes

Symptoms: redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities



Regulation EC No 1907/2006 Art.31

Productname: Brake Cleaner

Ref.Nr.: BDS000129_3_20141016 (EN)

Creationdate : Replaces:

16.10.14 Version : 2.0 BDS000129_20111223

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

Place in appropriate container

This material and/or its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Cleaners - Heavy duty

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:		-	-
carbon dioxide	124-38-9	TWA	5000 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm



Regulation EC No 1907/2006 Art.31

Productname: Brake Cleaner

Ref.Nr.: BDS000129_3_20141016 (EN)

Creationdate : Replaces:

16.10.14 Version : 2.0 BDS000129 20111223

National established exposure limits, United Kingdom			
carbon dioxide	124-38-9	TWA	5000 ppm
		STEL	15000 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	1500 ppm

8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

Air purifying respirator equiped with organic gas/vapor cartridge (type A)

hands and skin: Wear suitable protective gloves against chemicals

(neoprene)

eyes: Wear safety goggles.

Environmental protection: Avoid release to the environment.

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance : physical state : CO2 propelled liquid.

colour :Colorless.odour :Solvent.pH :Not applicable.Boiling point/range :55-120 °C

Flash point : < 0 °C (Closed Cup)

Evaporation rate : 2.8 (Ether=1) **Explosion limits : upper limit :** Not available.

lower limit: 0.9 %

Vapour pressure : Not available.

Relative density: 0.712 g/cm3 (@ 20°C).

Solubility in water : Insoluble in water

Auto-ignition :> 200 °CViscosity :Not available.

9.2. Other information

VOC: 685 g/l

SECTION 10: Stability and reactivity



Regulation EC No 1907/2006 Art.31

Productname:

Ref.Nr.:

Brake Cleaner

BDS000129_3_20141016 (EN)

Creationdate : Replaces:

16.10.14 Version : 2.0 BDS000129_20111223

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents may

induce chemical pneumonia.

Skin contact: Irritating to skin

Eye contact: Irritating to eyes

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol; isopropanol	67-63-0	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 5000 mg/kg
acetone; propan-2-one; propanone	67-64-1	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 2000 mg/kg
Naphtha (petroleum), hydrotreated light	64742-49-0	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 2000 mg/kg



Regulation EC No 1907/2006 Art.31

 Productname :
 Brake Cleaner
 Creationdate :
 16.10.14 Version : 2.0

 Ref.Nr.:
 BDS000129_3_20141016 (EN)
 Replaces:
 BDS000129_20111223

Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 25000 mg/m3
		LD50 derm.rat	> 2000 mg/kg
Naphtha (petroleum), hydrodesulfurized light (benzene <0.1%)	92045-53-9	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rat	> 2000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol; isopropanol	67-63-0	IC50 algae	> 1000 mg/l
		LC50 fish	> 1000 mg/l
		EC50 daphnia	> 1000 mg/l
acetone; propan-2-one; propanone	67-64-1	IC50 algae	> 100 mg/l
		LC50 fish	> 100 mg/l
		EC50 daphnia	> 100 mg/l
Naphtha (petroleum), hydrotreated light	64742-49-0	IC50 algae	10-30 mg/l
		LC50 fish	10-30 mg/l
		EC50 daphnia	1-10 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l
Naphtha (petroleum), hydrodesulfurized light (benzene <0.1%)	92045-53-9	IC50 algae	10-30 mg/l
		LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available



Regulation EC No 1907/2006 Art.31

Productname:

Brake Cleaner

Ref.Nr.: BDS000129_3_20141016 (EN)

Creationdate : Replaces:

16.10.14 Version : 2.0 BDS000129_20111223

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS (naphta's)

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally Yes

IMDG - Marine pollutant: Marine pollutant

IATA/ICAO - Environmentally

hazardous:

14.6. Special precautions for user

 ADR/RID - Tunnelcode:
 (D)

 IMDG - Ems:
 F-D, S-U

 IATA/ICAO - PAX:
 203

 IATA/ICAO - CAO
 203



Regulation EC No 1907/2006 Art.31

Productname: Brak

Ref.Nr.:

Brake Cleaner

BDS000129 3 20141016 (EN)

Creationdate : Replaces:

16.10.14 Version : 2.0 BDS000129 20111223

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

Regulation (EC) No 1907/2006 (REACH)

EU-directive 99/45/EC

Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases: R11: Highly flammable.

R36: Irritating to eyes. R38: Irritating to skin.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

*Explanation hazard statements: H225: Highly flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319 : Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

