# **RUST-OLEUM MATHYS**

best solutions in paints & coatings

# **PRODUCT DATA**

### **GREEN PAINT STRIPPER 2950**

#### DESCRIPTION

RUST-OLEUM® Paint Stripper 2950 is a paint dissolving material in an aerosol. Contains no methylene chloride.

#### **RECOMMENDED USES**

RUST-OLEUM Paint Stripper 2950 should be used for quick removal of old paint. RUST-OLEUM Paint Stripper 2950 is intended to remove all types of oil- and alkyd-based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden substrates.

As RUST-OLEUM Paint Stripper 2950 does not contain methylene chloride, acids, alkali's, NMP, biocides en conservation additives.

#### **TECHNICAL DATA**

Appearance: White, foamy layer

VOC-content: 750 g/l

Coverage

Theoretical: 2-3 m<sup>2</sup> per aerosol.

Practical: Practical coverage depends on many factors such as type of old coating and

shape of the substrate and material losses during application.

#### SURFACE PREPARTION

Remove loose coatings as much as possible by scraping.

## **DIRECTION FOR USE**

Remove cover cap. Shake vigorously before use. Hold the can approx. 10-20 cm from the substrate. Apply a uniform foam layer of Paint Stripper 2950; allow standing for minimal 15 minutes, and removing the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with cleaner/degreaser, fresh water or white spirit and allow drying completely before applying a coating.

## **APPLICATION CONDITIONS**

Temperature of air, substrate and aerosol between 10 and 35°C. Relative humidity below 85%.

### **REMARKS**

RUST-OLEUM Paint Stripper 2950 may affect plastic materials alike e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

#### SAFFTY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Page: 1 /1 - Ver. 00 PDS 2950-gb Issued: 15-11-08 The information contained herein is given in good faith. However, since application conditions are beyond our control, Rust-Oleum Netherlands B.V. cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

Andrews Coatings Ltd

Carver Building Littles Lane Wolverhampton West Midlands WV1 1JY

Tel. 01902 429190

info@rustoleumdirect.co.uk www.rustoleumdirect.co.uk