Issued: 07/03/2012 Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: TROJAN TDB SPRAY
Company name: Global Lubricants Ltd
13 Sandwell Business Development Centre
Oldbury Road
Smethwick,
West Midlands
B66 1NN
England

Tel: +44 (0)121 5443638 Fax: +44 (0)121 5446505

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredie	ents:		
Propellant	5000		TM
an Dutons	CAS	EEC (01,004,01,8)	%
•n-Butane	106-97-8	601-004-01-8	10-30 [F+] R12
•Propane	74-98-6	601-003-00-5	5-20 [F+] R12
Non-hazardous ingredients: Lubricants L			ants Ltd
Non-hazardous ingredients:			

• A mixture of Solvent Refined Mineral Oil, Chlorinated Paraffin, Sulphurised Ester and Lubricity Additives.

3. HAZARDS IDENTIFICATION

Main hazards,

Overexposure Effects:

Skin Contact: Will defat the skin and may cause irritation and redness after prolonged or repeated contact.

Eye Contact: Irritation.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Excessive quantities may cause headaches and drowsiness. Continued exposure will have a narcotic effect leading eventually to unconciousness.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact:

There may be irritation and redness at the site of contact.

Eve contact:

There may be irritation and redness. The eyes may water profusely.

Ingestion:

There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation:

There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact:

Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact:

Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation:

Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media:

Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards:

Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters:

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION Hazardous ingredients:



• PROPANE

WEL (8 hr exposure limit): 1800 mg/m3 WEL (15 min exposure limit): 7200 mg/m3

• BUTANE

WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eve protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Odour: Characteristic odour **Evaporation rate:** Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flash point°C: -5

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature. **Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids. **Haz. decomp. products:** In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Mammalian toxicity is considered to be moderately low.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Ultimately Biodegradable. Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

UN No. 1950 **Class:** 2

IMCO Class 9 ADR Class 2 Item 10 (b) 2

IATA Class 2 Subsidiary Risk 3 Packing Inst. 203

Packing Group II Trem Card 02



TM

ıbricants Ltd.

15. REGULATORY INFORMATION

Hazard symbols:

Extremely flammable.



Risk phrases:

R12: Extremely flammable.

R36/37/38: Irritating to eyes, respiratory system and skin.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases:

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S60: This material and its container must be disposed of as hazardous waste.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

Precautionary phrases:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2:

R12: Extremely flammable.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.