Safety	Data	Sheet
--------	------	-------

Regulation EC No 1907/2006 Art.31

Productname :	Flaw Detector Cleaner 1
Ref.Nr.:	BDS000130_3_20160211 (EN)

Creationdate : Replaces: 11.02.16 Version : 3.0 BDS000130_20141016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Flaw Detector Cleaner 1 Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Heavy duty

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Ambersil House - Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical:	Aerosols, category 1
_	Extremely flammable aerosol.
	Pressurised container: May burst if heated.
Health:	Skin irritation, category 2
	Causes skin irritation.
	Eye irritation, category 2
	Causes serious eye irritation.
	Specific target organ toxicity - single exposure, category 3
	May cause drowsiness or dizziness.
Environment:	Hazardous to the aquatic environment, chronic category 2
	Toxic to aquatic life with long lasting effects.

2.2. Label elements



Safety Data Sheet

Ref.Nr.: BDS000130_3_20160211 (EN) Replaces: BDS000130_20141016	Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0
	Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016

Labelling according to Regulation (EC) No 1272/2008

Product identifier:	Contains: hydrocarbons
Hazard pictogram(s):	
Signal word:	Danger
Hazard statement(s):	 H222 : Extremely flammable aerosol. H229 : Pressurised container: May burst if heated. H315 : Causes skin irritation. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness. H411 : Toxic to aquatic life with long lasting effects.
Precautionary statement(s):	 P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 : Do not spray on an open flame or other ignition source. P251 : Do not pierce or burn, even after use. P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area. P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501-2 : Dispose of contents/container to an authorised waste collection point.
Supplemental Hazard information:	None

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS- nr.	EC- nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C6-C7, n- alkanes,isoalkanes,cyclics,< 5% n- hexane	01- 2119475514- 35	-	921- 024-6	30- 60	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	в
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	01- 2119473851- 33	-	920- 750-0	10- 30	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H336,H304,H411	в
Hydrocarbons, C7, n- alkanes,isoalkanes, cyclic	01- 2119475515- 33	-	927- 510-4	10- 30	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225,H315,H336,H304,H411	в



Safety Data Sheet

Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016

carbon dioxide	-	124- 38-9	204- 696-9	5-10	Press. Gas	H280	A,G
propan-2-ol; isopropyl alcohol ;isopropanol	01- 2119457558- 25	67- 63-0	200- 661-7	<10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	в
acetone; propan-2-one; propanone	01- 2119471330- 49	67- 64-1	200- 662-2	<10	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	A
Explanation notes							
A : substance with Community workplace exposure limit							
B : substance with national establishe	d workplace expo	sure lim	nit				

G : exempted from the obligation to register in accordance with art.2(7)(a)of REACH Regulation No 1907/2006

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes :	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Contact with skin :	Take off contaminated clothing and wash before reuse. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Inhalation :	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Ingestion :	If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	Irritating to skin Symptoms : redness and pain
Eye contact :	Irritating to eyes Symptoms : redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment needed

General Advice :	If you feel unwell, seek medical advice (show the label where possible
	If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media



3 / 10

Safety Data Sheet	Regulation EC No 1907/2006 Art.31

Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material Place in appropriate container This material and/or its container must be disposed of as hazardous waste.

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition Take precautionary measures against static discharges Equipment should be earthed Use explosion-proof electrical/ventilating/lighting/.../equipment. Use only non-sparking tools. Do not breathe aerosols or vapours. Ensure adequate ventilation Avoid contact with skin and eyes. Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection.



4 / 10

Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0	
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016	

Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Cleaners - Heavy duty

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
carbon dioxide	124-38-9	TWA	5000 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
National established exposure limits, United Kingdom			· · · · · · · · · · · · · · · · · · ·
carbon dioxide	124-38-9	TWA	5000 ppm
		STEL	15000 ppm
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	TWA	400 ppm
		STEL	500 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	1500 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
	In all cases handle and use the product in accordance with good industrial hygiene practices.
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equiped with organic gas/vapor cartridge (type A)
hands and skin :	When handling the product wear chemical-resistant gloves (standard EN 374).
Recommended gloves:	(neoprene)
	The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Depending on amount and duration of use and the risk of contact with the



5 / 10

Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0	
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016	

	product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time.
eyes :	Wear safety goggles according to EN 166.
Environmental protection:	Avoid release to the environment.
_	Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product Apperance : physical state :	without propellant) CO2 propelled liquid.
colour :	Colorless.
odour :	Solvent.
pH :	Not applicable.
Boiling point/range :	55-120 °C
Flash point :	< 0 °C (Closed Cup)
Evaporation rate :	2.8 (Ether=1)
Explosion limits : upper limit :	Not available.
lower limit :	0.9 %
Vapour pressure :	Not available.
Relative density :	0.712 g/cm3 (@ 20°C).
Solubility in water :	Insoluble in water
Auto-ignition :	> 200 °C
Viscosity :	Not available.

9.2. Other information

VOC:

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

685 g/l

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials



6 / 10

Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	Causes skin irritation.
serious eye damage/irritation:	Causes serious eye irritation.
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	May cause drowsiness or dizziness.
STOT repeated exposure:	based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Irritating to skin
Eye contact :	Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 5000 mg/kg
acetone; propan-2-one; propanone	67-64-1	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 2000 mg/kg
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 2000 mg/kg
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 25000 mg/m3
		LD50 derm.rat	> 2000 mg/kg
Hydrocarbons, C7, n-alkanes,isoalkanes, cyclic	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l



Safety Data Sheet		Regulation EC No 1907/2006 Art.31		
Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0	
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016	

LD50 derm.rat

> 2000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
propan-2-ol; isopropyl alcohol ;isopropanol	67-63-0	IC50 algae	> 1000 mg/l
		LC50 fish	> 1000 mg/l
		EC50 daphnia	> 1000 mg/l
acetone; propan-2-one; propanone	67-64-1	IC50 algae	> 100 mg/l
		LC50 fish	> 100 mg/l
		EC50 daphnia	> 100 mg/l
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	-	IC50 algae	10-30 mg/l
		LC50 fish	10-30 mg/l
		EC50 daphnia	1-10 mg/l
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	-	LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l
Hydrocarbons, C7, n-alkanes,isoalkanes, cyclic	-	IC50 algae	10-30 mg/l
		LC50 fish	> 10 mg/l
		EC50 daphnia	3 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

None



8 / 10

Regulation EC No 1907/2006 Art.31

Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016
		•	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product :	This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.
National regulations :	Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS (naphta's)

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous: IMDG - Marine pollutant: IATA/ICAO - Environmentally hazardous: Yes

14.6. Special precautions for user

ADR/RID - Tunnelcode:	(D)
IMDG - Ems:	F-D, S-U
IATA/ICAO - PAX:	203
IATA/ICAO - CAO	203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.



Safety	Data	Sheet
--------	------	-------

Regulation EC No 1907/2006 Art.31

Productname :	Flaw Detector Cleaner 1	Creationdate :	11.02.16 Version : 3.0
Ref.Nr.:	BDS000130_3_20160211 (EN)	Replaces:	BDS000130_20141016
	,	•	_

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements. Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC. Regulation (EC) No 1907/2006 (REACH) EU-directive 99/45/EC Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation risk-phrases:	 R11: Highly flammable. R36: Irritating to eyes. R38: Irritating to skin. R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
*Explanation hazard statements:	 H225 : Highly flammable liquid and vapour. H280 : Contains gas under pressure; may explode if heated. H304 : May be fatal if swallowed and enters airways. H315 : Causes skin irritation. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness. H411 : Toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : 8.2. Exposure controls

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

