(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266

SITE FORM Number: 30000000000000000012648.002

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier : MR MUSCLE® Window & Glass (Professional)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Washing and cleaning products (including solvent based products)

Uses advised against : None identified

1.3 Details of the supplier of the :

safety data sheet

SC Johnson Ltd. Frimley Green

Camberley

GU16 7AJ

Telephone : +441276852000

E-mail address : ask.uk@scj.com

1.4 Emergency telephone

number

Consumer Care Center:

UK - 0800 353 353 Ireland - 1800 409 176

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EU) 1272/2008 with the correlation table 67/548/EEC or 1999/45/EC (Annex VII of CLP)

Hazard classification	Hazard category	Hazards identification
Skin irritation	Category 2	Causes skin irritation.
Eye irritation	Category 2A	Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 (CLP)



(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 3000000000000012648.002

Signal word

Warning

Hazard statements

(H315) Causes skin irritation.

(H319) Causes serious eye irritation.

Precautionary statements

(P101) If medical advice is needed, have product container or label at hand.

(P102) Keep out of reach of children.

(P305 + P351 + P338) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(P337 + P313) If eye irritation persists: Get medical advice/ attention.

(P264) Wash hands thoroughly after handling.

(P260) Do not breathe spray.

Additional Labelling

Use only in well-ventilated areas.

As with any household product avoid prolonged skin contact with this product For professional users only.

Detergents regulations

Contains

< 5% Anionic surfactants, perfume

2.3 Other hazards : None identified

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

mazar adas componem				
Chemical Name	CAS-No./EC No	Reg. No	Classification according to	Weight
			Regulation (EC) No	percent
			1272/2008 (CLP)	
2-hexyloxyethanol	112-25-4	01-2119486575-24	Acute toxicity	>= 1.00 - <
	203-951-1		Category 4	5.00
			H302	
			Acute toxicity	

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

2-hexyloxyethanol	112-25-4 203-951-1	01-2119486575-24	Category 4 H312 Skin corrosion Category 1B H314 Serious eye damage Category 1 H318 Acute toxicity Category 4 H302 Acute toxicity Category 4 H312 Skin corrosion Category 1B H314 Serious eye damage Category 1 H318	>= 1.00 - < 5.00
-------------------	-----------------------	------------------	--	---------------------

WEL substance propane-1,2-diol	57-55-6	01-2119456809-23		>= 0.10 - <
	200-338-0			0.50
acetic acid	64-19-7 200-580-7	01-2119475328-30	Flammable liquids Category 3 H226 Skin corrosion	>= 0.10 - < 0.50

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0
Revision Date 02.12.2016 Specificati

Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

	Category 1A	
	H314	
	Serious eye damage	
	Category 1	
	Н318	

Additional Information

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation : No special requirements

Skin contact : Take off all contaminated clothing immediately.

Wash off with soap and plenty of water.

Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

Eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

In the case of contact with eyes, rinse immediately with plenty of water and

seek medical advice. Rinse with plenty of water.

Get medical attention if irritation develops and persists.

Ingestion : If swallowed, do not induce vomiting: seek medical advice immediately and

show this container or label. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Eyes : Causes serious eye irritation.

No adverse effects expected when used as directed.

Skin effect : Causes skin irritation.

No adverse effects expected when used as directed.

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

Inhalation : No adverse effects expected when used as directed.

Ingestion : May cause irritation to mouth, throat and stomach.

May cause abdominal discomfort.

No adverse effects expected when used as directed.

4.3 Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable : Use extinguishing measures that are appropriate to local circumstances

and the surrounding environment.

Unsuitable : None identified

5.2 Special hazards arising from

the substance or mixture

Flammable liquid. Vapors are heavier than air and may travel to a source of

ignition and flash back.

In case of fire and/or explosion do not breathe fumes.

For large quantities of flammable liquids, consider containment to prevent

the spread of fire.

Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters : In the event of fire, wear self-contained breathing apparatus.

Wear suitable protective clothing and gloves.

Refer to current EN or National standard as appropriate.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours

can accumulate in low areas.

6.2 Environmental precautions : Outside of normal use, avoid release to the environment.

Use appropriate containment to avoid environmental contamination.

Prevent large amounts of product from entering drains. Prevent further leakage or spillage if safe to do so.

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

3000000000000012648.002

Do not flush into surface water or sanitary sewer system.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Clean residue from spill site.
Use only non-sparking equipment.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections : For personal protection see section 8.

For disposal considerations see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling : For personal protection see section 8.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the application area.

Wear personal protective equipment.

Keep away from sources of ignition - No smoking.

Take measures to prevent the build up of electrostatic charge.

7.2 Conditions for safe storage, including any incompatibilities

No smoking. Store in cool place. Do not freeze.

Keep out of the reach of children.

Store away from food, beverages and pet food. No decomposition if stored and applied as directed.

7.3 Specific end use(s) : Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

Washing and cleaning products (including solvent based products)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limit Values

Contains no substances with occupational exposure limit values.

Components	CAS-No.	mg/m3	ppm	Form of exposure	List
propane-1,2-diol	57-55-6	1,422	450 ppm	total particulate	UK_WELSTEL
		mg/m3		and vapour	
		30 mg/m3		particulate	UK_WELSTEL
		474	150 ppm	total particulates	UK_WELTWAS
		mg/m3		and vapour	

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number:

3000000000000012648.002

		10 mg/m3		particulate	UK_WELTWAS
acetic acid	64-19-7	25 mg/m3	10 ppm		EUOEL_TWAS

Refer to current EN or National standard as appropriate.

8.2 Exposure controls

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection : Wear suitable gloves.

Nitrile gloves – Thickness 0.12mm; Breakthrough time >2 hours. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Before removing gloves clean them with soap and water.

Eye/face protection : Safety glasses

Skin and body protection : Wash contaminated clothing before re-use.

Wear suitable protective clothing.

Other information : When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

Environmental Exposure Controls : Refer to section 6.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : green

Odour : Herbal

Odour Threshold : Test not applicable for this product type

pH : acidic

Melting point/freezing point : Test not applicable for this product type

Initial boiling point and boiling range : Test not applicable for this product type

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

Flash point : 56 °C

Evaporation rate : Test not applicable for this product type

Flammability (solid, gas) : Does not sustain combustion.

Upper/lower flammability or

explosive limits

: Test not applicable for this product type

Vapour pressure : Test not applicable for this product type

Vapour density : Test not applicable for this product type

Relative density : Test not applicable for this product type

Solubility(ies) : completely soluble

Partition coefficient: n-

octanol/water

Test not applicable for this product type

Auto-ignition temperature : Test not applicable for this product type

Decomposition temperature : Test not applicable for this product type

Viscosity, dynamic : Test not applicable for this product type

Viscosity, kinematic : Test not applicable for this product type

Explosive properties : Test not applicable for this product type

Oxidizing properties : Test not applicable for this product type

Other information : None identified :

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity : No dangerous reaction known under conditions of normal use.

10.2 Chemical stability : Stable under recommended storage conditions.

10.3 Possibility of hazardous

reactions

: None known.

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number:

3000000000000012648.002

10.4 Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

10.5 Incompatible materials : None known.

10.6 Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute oral toxicity

Name	Method	Species	Dose
Product	LD50		> 2,000 mg/kg
	Calculated		

Acute inhalation toxicity

Name	Method	Species	Dose	Exposure time
Product	LC50 (dust and		> 5 mg/l	
	mist)			
	Calculated			

Acute dermal toxicity

Name	Method	Species	Dose
Product	LD50		> 2,000 mg/kg
	estimated		

Acute oral toxicity

Name	Method	Species	Dose
2-hexyloxyethanol	LD50	Rat	738 mg/kg

Acute inhalation toxicity

Name	Method	Species	Dose	Exposure time
2-hexyloxyethanol	LC50 (vapour) Measured	Rat	> 0.787 mg/l	6 h

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

Acute dermal toxicity

Name	Method	Species	Dose
2-hexyloxyethanol	LD50	Rabbit	757.35 mg/kg

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Toxicity for reproduction : Based on available data, the classification criteria are not met.

STOT - single exposure : Based on available data, the classification criteria are not met.

STOT - repeated exposure : Based on available data, the classification criteria are not met.

Aspiration hazard : Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION

Product : The product itself has not been tested.

12.1 Toxicity

Toxicity to fish

Components	End point	Species	Value	Exposure time
2-hexyloxyethanol	LC50 static test	Pimephales promelas (fathead minnow)	140 mg/l	96 h
2-hexyloxyethanol	LC50 static test	Pimephales promelas (fathead minnow)	140 mg/l	96 h

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

propane-1,2-diol	LC50 static test Measured	Oncorhynchus mykiss (rainbow trout)	40,613 mg/l	96 h
	Chronic Toxicity Value QSAR	Fish	2,500 mg/l	30 d
acetic acid	LC50 static test	Lepomis macrochirus	75 mg/l	96 h

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
2-hexyloxyethanol	EC50 static test	Daphnia magna (Water flea)	145 mg/l	48 h
2-hexyloxyethanol	EC50 static test	Daphnia magna (Water flea)	145 mg/l	48 h
propane-1,2-diol	EC50 static test Measured	Ceriodaphnia dubia	18,340 mg/l	48 h
	NOEC semi-static test Measured	Ceriodaphnia sp.	13,020 mg/l	7 d
acetic acid	EC50 static test	Daphnia magna (Water flea)	65 mg/l	48 h

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
2-hexyloxyethanol	EC50 static test	Desmodesmus subspicatus (green algae)	147.128 mg/l	96 h
2-hexyloxyethanol	EC50 static test	Desmodesmus subspicatus (green algae)	147.128 mg/l	96 h
propane-1,2-diol	EC50 static test Measured	Scenedesmus capricornutum (fresh water algae)	19,000 mg/l	96 h
acetic acid	EC50 Static	Skeletonema	> 300.82 mg/l	72 h

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

|--|

12.2 Persistence and degradability

Component	Biodegradation	Exposure time	Summary
2-hexyloxyethanol	96.8 %	20 d	Readily biodegradable
2-hexyloxyethanol	96.8 %	20 d	Readily biodegradable
propane-1,2-diol	81.7 % Measured	28 d	Readily biodegradable
acetic acid	96 %	20 d	Readily biodegradable

12.3 Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n-Octanol/water (log)
2-hexyloxyethanol	5.8 estimated	1.97
2-hexyloxyethanol	5.8 estimated	1.97
propane-1,2-diol	0.09	-1.07
acetic acid	3.16	-0.17

12.4 Mobility in soil

Component	End point	Value
2-hexyloxyethanol	Кос	10 estimated
2-hexyloxyethanol	Кос	10 estimated
propane-1,2-diol	Кос	2.9 Measured
acetic acid	Кос	1.15

12.5 Results of PBT and vPvB assessment

Component	Results
2-hexyloxyethanol	Not fulfilling PBT and vPvB criteria

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

2-hexyloxyethanol	Not fulfilling PBT and vPvB criteria
propane-1,2-diol	Not fulfilling PBT and vPvB criteria
acetic acid	Not fulfilling PBT and vPvB criteria

12.6 Other adverse effects None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Disposal should be in accordance with local, state or

national legislation.

Please recycle empty packaging.

Packaging : Do not re-use empty containers.

SECTION 14: TRANSPORT INFORMATION

Land transport

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

This safety datasheet complies with the requirements of Regulation (EC)

No. 1907/2006.

regulations/legislation specific for

the substance or mixture

SECTION 16: OTHER INFORMATION

If applicable, revision(s) are noted by the bold bars || in left-hand margin.

(according to Regulation (EC) No. 2015/830)



MR MUSCLE® Window & Glass (Professional)

Version 1.0 Revision Date 02.12.2016 Print Date 27.03.2017 Specification Number: 350000024266 SITE FORM Number: 30000000000000012648.002

Key abbreviations or acronyms used

EC - European Community

EEC - European Economic Community

CLP - Classification Labelling & Packaging

EN – European Standard or European Norm

PBT – Persistent, Bioaccumulative & Toxic

vPvB – very persistent, very bioaccumulative

UN - United Nations

Evaluation methods

Unless otherwise stated in section 11, the procedure used to derive the human health classification is the relevant calculation method according to CLP regulation (EC) No 1272/2008 as amended.

Unless otherwise stated in section 12, the procedure used to derive the environmental classification is the summation of the classified components method according to CLP regulation (EC) No 1272/2008 as amended.

Full text of H-Statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.