



SAFETY DATA SHEET
DELTA D301 QUICK STEEL SYRINGE
ACTIVATOR

Page: 1

Compilation date: 25/05/15

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: D301 QUICK STEEL SYRINGE ACTIVATOR

Product code: D301

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Epoxy hardener preparation

1.3. Details of the supplier of the safety data sheet

Company name: Delta Adhesives Limited
Units 39-40
Claycliffe Business Park
Cannon Way, Barugh Green
Barnsley
South Yorkshire
S75 1JU

Tel: +44 (0) 1226 381571

Fax: +44 (0) 1226 381722

Email: info@delta-adhesives.co.uk

1.4. Emergency telephone number

Emergency Telephone Number: +44 (0) 1226 381571 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: This product has no classification under CHIP.

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET
D301 QUICK STEEL SYRINGE ACTIVATOR

Page: 2

Hazardous ingredients:

LIMESTONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-279-6	1317-65-3	Substance with a Community workplace exposure limit.	-	20-40%

BARIUM SULFATE

-	7727-43-7	Substance with a Community workplace exposure limit.	-	10-20%
---	-----------	--	---	--------

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

202-013-9	90-72-2	Xn: R22; Xi: R36/38	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-5%
-----------	---------	---------------------	---	------

SILICONE DIOXIDE

231-545-4	7631-86-9	Substance with a Community workplace exposure limit.	Aquatic Chronic 3: H412	1-5%
-----------	-----------	--	-------------------------	------

TITANIUM DIOXIDE

-	13463-67-7	Substance with a Community workplace exposure limit.	-	1-5%
---	------------	--	---	------

MAGNESIUM CARBONATE

208-915-9	546-93-0	Substance with a Community workplace exposure limit.	-	1-5%
-----------	----------	--	---	------

TALC

238-877-9	14807-96-6	Substance with a Community workplace exposure limit.	-	1-5%
-----------	------------	--	---	------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Get medical attention if any discomfort continues.

Eye contact: Bathe the eye with running water for 15 minutes. If symptoms persist seek medical attention

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. Never give anything by mouth to an unconscious person. If unconscious and breathing is OK, place in the recovery position.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position.

[cont...]

SAFETY DATA SHEET
D301 QUICK STEEL SYRINGE ACTIVATOR

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides. In combustion emits toxic fumes of sulphur oxides.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Ensure adequate ventilation
Avoid skin and eye contact. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Smoking, eating, drinking and the preparation of foodstuffs prohibited where materials are stored or handled.

[cont...]

SAFETY DATA SHEET
D301 QUICK STEEL SYRINGE ACTIVATOR

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. For safe storage, store between 5-30 degC. Keep container tightly closed. Keep in original container.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Part B (catalyst) of a two pack, epoxy repair paste, to be used only with the corresponding Part A (resin) component.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

LIMESTONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	4 mg/m3	-

BARIUM SULFATE

UK	-	-	4 g/m3	-
----	---	---	--------	---

SILICONE DIOXIDE

UK	-	-	2.4 mg/m3	-
----	---	---	-----------	---

TITANIUM DIOXIDE

UK	-	-	4 mg/m3	-
----	---	---	---------	---

MAGNESIUM CARBONATE

UK	-	-	4 mg/m3	-
----	---	---	---------	---

TALC

UK	-	-	1 mg/m3	-
----	---	---	---------	---

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. If product is handled in an open system, the use of process enclosures, local exhaust ventilation, and/or other engineering controls should be considered to control airborne levels to below recommended exposure limits, or below acceptable levels.

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Protective clothing.

[cont...]

SAFETY DATA SHEET
D301 QUICK STEEL SYRINGE ACTIVATOR

Page: 5

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Off-white

Odour: Sulphurous.

Solubility in water: Insoluble

Flash point°C: Does not flash

Relative density: 1.69

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Epoxy resins Amines.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon monoxide. In combustion emits toxic fumes of sulphur oxides. In combustion emits toxic fumes of nitrogen oxides.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORL	RAT	LD50	1200	mg/kg
SKN	RAT	LD50	1280	mg/kg

[cont...]

SAFETY DATA SHEET
D301 QUICK STEEL SYRINGE ACTIVATOR

Page: 6

SILICONE DIOXIDE

IPR	RAT	LD50	50	mg/kg
IVN	RAT	LD50	15	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

[cont...]

SAFETY DATA SHEET
D301 QUICK STEEL SYRINGE ACTIVATOR

Page: 7

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

R22: Harmful if swallowed.

R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.